tritium acam b801

Features:

- Advanced DPS(Digital Pixel System) Technology
- No Smear and Minimum blooming problem
- Strong capability to catch full clean picture under back light or extreme lighting environment.
- CS mount or C mount with 5mm adaptor ring lens
- 480 TV lines
- Suitable for surveillance of lobby entrance / ATM / Car Plate Identification
- Full O.S.D.(On-Screen-Display) menu for multiple functions

Camera Specification:
Sensor: ***1/3" COLOUR DPS SENSOR*** *BLC:* ****SEE EXPOSURE MODE**** *Resolution*: ***PAL: 720(H)X540(V)*** *Horizontal Resolution:* ***480 TV LINES*** *Sync System:* ***INTERNAL SYNC. LINE-LOCK(AC INPUT REQUIRED)*** *S/N Ratio:* ***OVER 48db*** *AGC:* ***ON/OFF SWITCH*** *Min. Illumination:* ***1.0 LUX / F1.2*** *Exposure Mode:* ***5 MODES SELECTABLE ON SCREEN*** ***INDOOR MODE*** ***OUTDOOR MODE*** ***FLOUR MODE*** ***BACKLIGHT MODE*** ***USER MODE*** *Slow Shutter:* ***ON/OFF LEVEL 2~32*** *Camera ID Symbol:* ***12 CHARACTER TITLE GENERATOR***
Lens:
Lens Mount: ***CS MOUNT OR C MOUNT WITH 5mm ADAPTOR RING LENS*** *IRIS Level:* ***DIRECT DRIVE A.I. ONLY*** *D/D Lens IRIS Level:* ***LEVEL: -34~20***
Audio:
*Audio****: N/A***
Display:
Video Output: ***1.0Vp-p, 75Ω*** *S-Video:* ***MINI DIM S-VIDEO, Y:1.0Vp-p, 75Ω C:286mV, 75Ω (NTSC) C:330mV, 75Ω (PAL)***
Networking:
Operation: ***N/A***
Electrical:
POWER SOURCE: ***DC 12V / AC 24V LINE LOCK.*** *CONSUMPTION:* ***7W MAX.***
Environmental:
Working Temperature: ***0°C TO +40°C***
Physical:
Waterproofing Criterion: *Dimension:* ***60(W)x 50(H)x 118(D)mm*** *Weight:* ***APPROX. 370g.***